

Product Name :
Drag Co Efficient Apparatus

Product Code :
Transfer0022



Description :

Drag Co Efficient Apparatus

Technical Specification :

Drag Co Efficient Apparatus

The apparatus has been designed to introduce students to the fundamental characteristics of the behavior of the particle system, in particular the relationship between the drag coefficient of falling particles and their Reynolds number value. Particles covering a range of sizes and densities are supplied and the experiments are conducted by allowing single particles to fall through a number of different liquids contained in vertical glass tube. The rate of fall of the particle is determined by timing their passage between two marks on the walls of the glass tubes. Observation of particle movement is aided by the provision of a shielded fluorescent tube light

mounted on the backboard. Particles can be removed from the bottom of the tubes without the necessity of draining the liquid. A valve system is provided at the bottom of each tube to allow the particles to be removed with the minimum loss of liquid.

Experiment:

- To measure the drag co-efficient
- To plot the graph between drag co-efficient vs. Modified Reynolds number
- To study the motion of a solid particle through a liquid

Utilities Required:

- Electricity supply 100 watts, 220 , 1 phase
- Floor Area 0.75 m x 1.5 m
- Liquids of different viscosity

Electrical and Electronics

Website: www.electricelectronicsindia.com, **Email:** export@electricelectronicsindia.com

Address: 6148/6, Guru Nanak Marg, Ambala Cantt, Haryana, India, **Phone:** +91-0171-2643080, 2601773